

DS-19A08-01BN



- Supports 8 wired onboard inputs, expandable to 256, 4 onboard outputs expandable to 256
- Supports up to 32 keypads, 32 keyfobs
- Supports multiple communication methods: PSTN + Wired IP
- Supports up to 64 wireless zones using transceiver DS-PM-RSWR



▪ Specification

Software features	
Schedule	Support (Normal Schedule/Preferential Schedule)
Configuration tools	IVMS4200/Hik-Central/Keypad
Firmware update tools	Remote upgrade via network
User	1 installer code, 1 master code and 199 operator code
Area	8
Hardware features	
Printer interface	1 RS-232
PSTN	1, PSTN expander interface
Tamper-Proof	Tampering alarm
Communication interface	1 RS485 Half-duplex
Network interface	1, RJ45 10M/100M Ethernet Interface
Bus	MBUS
Electrical characteristics	
Power supply	AC220V
Power interface	AC220V
Operation humidity	10% to 90%
Operation temperature	-10°C to 55°C
Power consumption	≤ 60W (Load Power ≤ 40W)
General	
Dimension(WxHxD)	370 mm × 320 mm × 86 mm
Application scenario	mainly applied to various industries such as finance, judicature, education, transport, electricity as well as shopping malls, stores, residences, apartments, communities and so on
Shell material	metal
Color	lightgray
Weight	< 3.5 kg
Device management	
Alarm output	256
Alarm input	256
Zones	256
Relay output	4
Keypad	32
Sounder output	1
Keyfob	32
Repeater	4
Report method	
Protocol	SDK, CID (DC05), SADP, DHCP

▪ Available Model

DS-19A08-01BN

