

DS-KB2421T-IM

Four-Wire Analog Door Station

HIKVISION[®]



Key Feature

- Hands-free video intercom communication
- Supports two door stations simultaneously in the intercom system
- Self-adaptive IR supplement (with photoresistor)
- One-touch calling
- Pinhole camera with 1920 x 1080 @ 25 fps
- Unlock controlling
- Anti-oxidant aluminium alloy
- Convenient installation and easy operation

Power Consumption	≤5 W
Working Temperature	-30° C to 70° C (-22° F to 158° F)
Working Humidity	10% to 90%
Dimensions (L x W x H)	195.8 mm × 132.8 mm × 18.39 mm (7.7" × 5.2" × 0.7")
Material	Zinc alloy

Available Model

DS-KB2421T-IM

Specification

Video parameters	
Camera	1/2.7" CMOS
Resolution	1920 x 1080
Video Frame Rate	PAL: 25 fps
FOV	Horizontal: 66.2° , Vertical: 37.2°
Audio parameters	
Audio Input	Built-in omnidirectional microphone
Audio Output	Built-in loudspeaker
Audio Quality	Noise suppression and echo cancellation
Device interfaces	
Four-wire Interface	1-ch video input, 1-ch audio input/output, 1-ch power supply, 1-ch grounding
I/O Output	1 relay output
General	
Power Supply	12 VDC

Dimension



