



Key Feature

- Modular door station Touch & Display module, needs mounting bracket
- 4-inch touch screen, IP65, IK8
- Dial number display, pin code & card unlock, contact list & advertisement display
- Stores and searches contact list
- Multiple languages

Specification

| System parameters | |
|----------------------------|---|
| Operating system | Linux |
| ROM | 32 MB |
| RAM | 128 MB |
| Display parameters | |
| Screen size | 4-inch |
| Type | IPS touch screen |
| Resolution | 480 x 480 |
| Audio parameters | |
| Audio compression standard | / |
| Audio input | / |
| Audio output | Buzzer |
| Audio compression bitrate | / |
| Audio quality | / |
| Volume adjustment | / |
| Power output | / |
| Network parameters | |
| Wireless network | Only AP mode |
| Authentication | |
| Card reading frequency | 13.56 MHz |
| Card reading distance | 2 cm |
| Card type | Mifare card |
| Device interfaces | |
| TF card | Reserved |
| DIP switch | 8 bits |
| Cascade interface | 2 |
| General | |
| Installation | Surface, flush |
| Protective level | IP65, IK8 |
| Working temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Working humidity | 10% to 95% (no-condensing) |
| Dimensions | 100 mm × 100 mm × 35 mm (3.94" × 3.94" × 1.38") |
| Power supply | 12 VDC, supplied by the main module |
| Power consumption | ≤ 10 W |

Available Model

DS-KD-TDM

Dimension

