

DS-PDC15-EG2

DS-PDC15-EG2 series of curtain detectors are equipped with dual-element infrared sensor and narrow angle lens. Up to 15m range with full vertical coverage allows the detector be capable of protecting any kind of entries/windows.

- Up to 15 m detection range
- Digital temperature compensation
- Selectable EOL resistors for alarm and tamper-proof wiring
- Sealed optics preventing insect interference
- Global certifications available (EN Grade2/CE/FCC/CB/IC/RCM)
- 9 to 16 V wide voltage adaptation with polarity reverse connection protection
- Wall/Ceiling-mounting brackets available (sold separately)

▪ Specification




| Detection Performance | |
|----------------------------------|-----------------------------------|
| Detection Method | Passive Infrared |
| Detection Range | 15 m |
| Detection Angle | 6.3° |
| Detection Zones | 18 |
| Detectable Speed | 0.3 ~ 2 m/s |
| White Light Filter | 6500lux |
| Digital Temperature Compensation | Support |
| Creep Zone Protection | Support |
| Feature | |
| Digital Processing | Support |
| Sealed Optics | Support |
| Tamper Protection | Front |
| Interface | |
| Alarm Output | Normally Closed |
| LED Indicator | Blue(Alarm) |
| Transmission | |
| Transmission Method | Wired |
| Electrical Characteristics | |
| Power Supply | 9 - 16 VDC |
| Typical Voltage | 12 VDC |
| Power Consumption | 11mA Max |
| General | |
| Operation Temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Storage Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Operation Humidity | 10% to 90% |
| Dimension(W x H x D) | 65.4 mm x 86.8 mm x 45.5 mm |
| Weight | 68 g |
| Mounting Height | 2.4 m to 3.6 m |
| Mounting Method | Wall |
| Application Scenario | Indoor |
| Bracket | Optional wall & ceiling accessory |

▪ Available Model

DS-PDC15-EG2

▪ **Accessory**

▪ **Optional**

| DS-PDB-IN-Ceiling bracket Internal ceiling mounted bracket | DS-PDB-IN-Wall bracket Internal wall mounted bracket | DS-PDB-IN-Universal bracket Internal universal bracket |
|---|---|---|
|  |  |  |

