

# DS-PDCM15PF-IR Camera Module



Camera module that works with our newly released wireless outdoor Tri-tech detector, built-in CMOS high quality color camera that provide you an ideal solution for video verification, both users and CMS can verify alarms day and night by viewing real-time images captured by this camera module for fast and accurate response to real alarm events

- 1/2.7" Progressive Scan CMOS
- 2.0 mm fixed lens
- 3D Digital Noise Reduction
- Easy Installation
- The direction of the Angle can be adjusted to fit the TT Detector's Angle
- Protection Level IP66





## Specification

Detection Performance	
Detection Method	Video Verification
Feature	
Digital Noise Reduction	3D
Focal length	2.0mm@F2.25
Video	
Field Angle	137.2°(H), 80.1°(V)
Image Type	JPEG
Resolusion	640*480,320*240,160*120
Fill Light	Infrared Light
Fill Range	15m
Day/Night Switch	Auto
Interface	
Communication Interface	1 12-Bit Data Interface
<b>Electrical Characteristics</b>	
Power Supply	3 VDC
Power Consumption	1200mA
General	
Operation Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Storage Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Operation Humidity	10% to 90%
IP Rate	IP66
Dimension(WxHxD)	74.1mm x 72.35mm x 53mm
Weight	155g

#### Available Model

DS-PDCM15PF-IR

#### Accessory

### Optional

DS-PDTT15AM-L	DS-PDTT15AM-L
M-WB	M-WE



117/8, Changwatthana 10, LakSi, Bangkok 10210

Phone: (66 2) 094-0800 E-mail: sale@bainisys.com

Line Chat: @Bainisys

