

DS-PDEB2-EG2-WB(B) Wireless Emergency Button

The panic button is a updated version of current wireless emergency button with water proof feature. It is flexible to be fixed in any places even in strong humid environment.

- Dual effective emergency button
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission
- IP66 water proof



▪ Specification

| Feature | |
|-----------------------------------|---|
| Button | 2 |
| Tamper Protection | Front,Rear |
| Environment Temperature Indicator | Support |
| Signal Strength Indicator | Support |
| Interface | |
| LED Indicator | Blue(Alarm) |
| Transmission | |
| Transmission Technology | Tri-X Wireless |
| Transmission Method | Two-Way RF Wireless |
| Transmission Frequency | 433MHz |
| Transmission Security | AES-128 Encryption |
| Transmission Range(Free Space) | 800m |
| Frequency Hopping | Support |
| Enrolling Method | Power up,Remote ID,QR Code |
| Electrical Characteristics | |
| Standard Battery Life | 3 years in work status (being triggered 20 times per day) |
| Power Supply | Battery Powered |
| Battery Type | CR2450 x 1 |
| Typical Voltage | 3V |
| General | |
| Operation Temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Storage Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Operation Humidity | 10% to 90% |
| IP Rate | IP66 |
| Dimension(WxHxD) | 63.8mm×63.8mm×19mm |
| Weight | 58.5g |
| Mounting Method | Wall |
| Application Scenario | Indoor Humid environment especially |

▪ Available Model

DS-PDEB2-EG2-WB(B)

