

DS-PDSMK-S-WB

Wireless Photoelectric Smoke Detector



- High quality chamber with photoelectric sensor
- 10 years battery life

▪ Specification

	Model	DS-PDSMK-S-WB
Detection Performance	Detection Method	Chamber With Photoelectric Sensor
Feature	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	Power Switch	Power Up Enrolling
	LED Indicator	Red (Alarm)
	Buzzer	≥ 85dB @ 3 m
Transmission	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	433 MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	800 m
	Enrolling Method	Power up, Remote ID, QR Code
Electrical Characteristics	Standard Battery Life	10 years in standard standby status
	Power Supply	Battery Powered
	Battery Type	Non Replaceable CR17450 x 1
	Typical Voltage	3 V
General	Operation Temperature	-10 °C to 60 °C (14 °F to 140°F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(Dia. x D)	φ102 × 35 mm
	Weight	125 g
	Mounting Method	Ceiling
	Application Scenario	Indoor

▪ Available Model

DS-PDSMK-S-WB

