

## DS-PDSMK-S-WE

### Wireless Photoelectric Smoke Detector

- High quality chamber with photoelectric sensor
- 10 years battery life



#### ▪ Specification

	Model	DS-PDSMK-S-WE
<b>Detection Performance</b>	Detection Method	Chamber With Photoelectric Sensor
<b>Feature</b>	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
<b>Interface</b>	Power Switch	Power Up Enrolling
	LED Indicator	Red (Alarm)
	Buzzer	≥ 85 dB @ 3 m
<b>Transmission</b>	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	868 MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	800 m
	Enrolling Method	Power up,Remote ID,QR Code
<b>Electrical Characteristics</b>	Power Supply	Battery Powered
	Battery Type	Non Replaceable CR17450 x 1
	Typical Voltage	3 V
	Standard Battery Life	10 years in standard standby status
<b>General</b>	Operation Temperature	-10 °C to 60 °C (14 °F to 140°F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(Dia. x D)	φ102 × 35 mm
	Weight	125 g
	Mounting Method	Ceiling
	Application Scenario	Indoor

#### ▪ Available Model

DS-PDSMK-S-WE

