

DS-PDWL-E-WE



- Water-proof design for multiple use applications
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Frequency hopping against jamming for reliable transmission
- External probe included

▪ Specification

Model		DS-PDWL-E-WE
Feature	Digital Processing	Support
	Tamper Protection	Front,Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	LED Indicator	Blue (Alarm)
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	868MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1.2Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code



Electrical Characteristics	Typical Voltage	3 V
	Power Supply	Battery Powered
	Battery Type	CR2450 x 1
	Standard Battery Life	3 years in work status (being triggered 20 times per day)
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	IP Rate	IP66
	Dimension(Wx HxD)	62.4mm × 62.4mm × 14.6mm
	Weight	85.5g
	Mounting Method	Wall, Surface
	Application Scenario	Indoor standalone/with included probe

▪ **Available Model**

DS-PDWL-E-WE



117/8, Changwatthana 10, LakSi, Bangkok 10210
 Phone : (66 2) 094-0800
 E-mail : sale@bainisys.com
 Line Chat : @Bainisys

