

HIKVISION

DS-PK-L Series

LCD Keypad

The DS-PK-L series keypad is used with DS-19A series hybrid security control panel for system programming and setting up. The DS-PK-LRT is with built-in wireless transceiver and card reader, which can work with keyfob and tag for arming/disarming.



AVAILABLE MODEL

DS-PK-L	(LCD screen)
DS-PK-LRT	(LCD screen, keyfob & tag supported, 433MHz/868MHz optional)

MAIN FEATURES

- 80 × 25 mm LCD screen display
- Supports arming and disarming by swiping cards (DS-PK-LRT)
- Supports remote arming and disarming via keyfob (DS-PK-LRT)
- One-push to arm
- Supports displaying zone name on the LCD screen
- Supports displaying the real-time system status by LED indicator
- Supports displaying the real-time zones status and events by LCD screen
- Detachable wiring terminal for easy wiring and installation
- Temper proof: cover and wall

SPECIFICATIONS

Model	DS-PK-L	DS-PK-LRT
Numeric key	12 (0 1 2 3 4 5 6 7 8 9 * #)	
Function Key	8 Function Keys (Project, Query, Panic, Bypass, Fire, One-push to arm, Scroll up, Scroll down)	
Indicator	Fault(Orange ●), Network(Green ●), Alarm(Red ●), Armed/Disarmed(Blue ●), Set(Red/Green ● / ●)	
Tamper-Proof	Supported	
Uplink Communication	RS-485	
Sound Prompt	Buzzer	
Wireless frequency	N/A	433MHz/868MHz optional
Keyfob	N/A	Supported
Tag	N/A	Supported
Power	12V DC	
Power Consumption	1.8 W	
Operation Temperature	- 10 °C to + 55 °C (14 °F to 131 °F)	
Operation Humidity	10% ~90%	
Weight	272g	



117/8, Changwatthana 10, LakSi, Bangkok 10210
 Phone : (66 2) 094-0800
 E-mail : sale@bainisys.com
 Line Chat : @Bainisys

