

DS-PK1-LT-WE Wireless Keypad



- 868MHz two-way wireless communication
- LCD screen and LED to indicate system status
- System configuration through LCD screen
- Multiple operations like stay/away arm, disarm, silent alarm, output control
- One-Push fire alarm, panic alarm, and medical alarm
- Full touch key design with LED backlight
- Fully remote configurable through App



▪ Specification

| Hardware features | |
|----------------------------|---|
| Tag reader built in | Supported |
| Serial port | 3 |
| Tamper-Proof | Supported, front and rear |
| Buzzer | Supported |
| Power switch | Power on/off |
| Electrical characteristics | |
| Battery type | Four CR123 batteries |
| Operation humidity | 10% to 90% |
| Operation temperature | -10 °C to 55 °C |
| Battery life span | Standby time more than two years |
| Power consumption | Quiescent current: 80 uA Max current: 300 mA Voltage: 3 V |
| Wireless transmission | |
| RF frequency | 868 MHz |
| RF modulation | 2GFSK |
| RF distance | 1200 m (open area) |
| Wireless technology | Tri-X Wireless Technology |
| Display | |
| Numeric key | Number key: 0 to 9 Function key: *, #, Query, Away arm, Stay arm, Disarm, Output, Project, Right, Left |
| LED indicator | Fault(orange), Enrollment/Signal (red/green), Arm(blue), Disarm(green), Alarm (red) |
| General | |
| Installation method | Wall mounting |
| Dimension(W×H×D) | 174.63 mm × 109.62 mm × 25.25 mm |
| Weight | With batteries: 348 g Without batteries: 282 g |
| Color | White |

▪ Available Model

DS-PK1-LT-WE

