

DS-PKA-WLM Wireless Keypad

The DS-PKA-WLM series wireless keypad can connect to security control panel for alarm control and operation. It can also notice alarm by indicator and buzzer.

Available Models

DS-PKA-WLM

Features

- 433/868 MHz two-way wireless communication
- AES-128 encryption
- Operation: Arming, disarming, alarm clearing, etc.
- Arming or disarming with card
- Patrol card (different from the arming/disarming card) checking in
- Full touch screen design with LED backlight

Specifications

| Model | | DS-PKA-WLM-433 | S-PKA-WLM-868 |
|------------------------|-----------------------|---------------------------------------------------------------------------------------|---------------|
| RF | RF speed | 10.0 kbps/4.8 bps | |
| | RF frequency | 433 MHz/868 MHz | |
| | RF modulation | 2GFSK | |
| | RF distance | 800 m (open area) | |
| | RF power | 10 dBm | |
| | TAMPER switch | 1 | |
| | RF module | Communicates with wireless control panel | |
| Interface & component | Card | Supports standard IC card swiping | |
| | Buzzer | 1 | |
| | Serial port | 1, reserved | |
| | Numeric | 10 keys: 0 to 9 | |
| Application & protocol | Function key | 6 function keys: fire alarm, away arming, stay arming, disarming, delete, and confirm | |
| | Protocol | HIK wireless protocol: Access to wireless control panel, two-way communication | |
| | Power | 3 VDC power input | |
| Electrical & battery | Battery type | 4 AA batteries | |
| | Battery life span | 3 years | |
| | Operation humidity | 10% to 90% (No condensing) | |
| Others | Operation temperature | -10 °C to +55 °C (-4 °F to +122 °F) | |
| | Color | White | |
| | Dimension | φ131.5 mm (5.2"); height: 23 mm (0.9") | |



