

## DS-PKG Wired Keypad

DS-PKG series wired keypad can connect to security control panel for alarm control and operation. It can also notice alarm by indicator and buzzer.



### Available Models

- DS-PKG-H4L: 4 inputs LED keypad
- DS-PKG-H8L: 8 inputs LED keypad

### Features

- Operation: arming, disarming, alarm clearing, bypass, bypass restoring, partition control, control panel status query etc.
- Tamper-proof
- Function key: project, panic, status, and bypass
- Real time zone status display



## Specifications

Model		DS-PKG-H4L	DS-PKG-H8L
Interface & component	TAMPER switch	1	
	Buzzer	1	
	Indicator	Control panel status indicator: 2, work (red/green), arm/disarm (red/green)	
		Zone status indicator: 4, red/green	Zone status indicator: 8, red/green
	Numeric	12 keys: 0 to 9, *, and #	
	Function key	4 function keys: project, panic, status, and bypass	
Display	Screen	LED	
Application & protocol	Protocol	RS-485	
Function	Function	Arming, disarming, alarm clearing, bypass, bypass restoring, partition control, control panel status query etc.	
Others	Operation humidity	10% to 90% (No condensing)	
	Operation temperature	-10 °C to +55 °C (-4 °F to +122 °F)	
	Weight	149g	
	Dimension	133.9 mm (5.3") x 74.9 mm (1.9") x 27.7 mm (1.1")	


**BAINISYS**

117/8, Changwatthana 10, LakSi, Bangkok 10210

Phone : (66 2) 094-0800

E-mail : sale@bainisys.com

Line Chat : @Bainisys

