

DS-PSG-WO

Wireless Outdoor Siren

The wireless outdoor siren is used to connect to security control panel for instant notice when an alarm is triggered.



Available Model

- DS-PSG-WO-433
- DS-PSG-WO-868

Key Feature

- 433/868 MHz two-way wireless communication
- Reports exception automatically
- AES-128 encryption
- Adjustable volume: low, medium, and high
- Front and rear panel tamper-proof
- Protection level: IP65
- Outdoor installation
- Flashing blue LED for alarm indication
- 3 kinds of alarm sounds: fire alarm, intrusion alarm, and panic alarm



Specifications

Model		DS-PSG-WO-433/DS-PSG-WO-868
RF	RF frequency	433/868 MHz
	RF modulation	2GFSK
	RF speed	10 kbps/4.8 kbps
	RF power	10 dBm
	RF method	Two-way communication
	RF encryption	AES-128
	RF distance	800 m (open area)
Electrical & battery	Power	4 CR123A Batteries (default) or 12 VDC
	Consumption	Static consumption: < 20 uA
	Battery life span	5 years in stand-by status
Interface and component	Learnt button	1
	TAMPER switch	Front and rear panel tamper-proof
	Indicator	Blue (on front panel), Green/Red (on PCB)
	Buzzer	1, Decibel: 110 dB
Others	Operation temperature	-25 °C to +60 °C (-13 °F to +140 °F)
	Operation humidity	10% to 90% (no condensing)
	Color	White and blue
	Material	PC+ABS
	Dimension (W × H × D)	220.5 × 205.2 × 46 mm (8.68" × 8.08" × 1.81")
	Protection level	IP65
	Installation	Wall mounting



BAINISYS

117/8, Changwatthana 10, LakSi, Bangkok 10210

Phone : (66 2) 094-0800

E-mail : sale@bainisys.com

Line Chat : @Bainisys

