HIKVISION



DS-PD2-P25-W consists of a PIR, which works by constantly monitoring the infrared energy levels around a corridor. The detector will recognize any changes caused by the entry of an intruder and inform the panel to go into an alarm condition.



AVAILABLE MODEL

DS-PD2-P25-W

MAIN FEATURES

- Long range coverage pattern
- Two-way Wireless technology
- Selectable sensitivity
- Digital temperature compensation technology
- Sealed optics
- Signal Strength Indicator

SPECIFICATION

Wireless PIR Detector	
Detection Range	25m, detection angle: 8°
Detection Speed	0.3m/s ~ 3.0m/s
Power Supply	1 imes CR123A, 3.0V, up to 2 years Battery life
Operation Temperature	-10°C ~ +40°C
Dimension(H*W*D)	117mm*69mm*50mm
Weight	125g (without bracket)
Installation Environment	Indoor
Installation Height	1.8m ~ 2.4m
Transmission Frequency	433MHz
Transmission Range	800m in open space

*Including 1 x Ceiling mounting bracket, 1 x Wall mounting bracket



117/8, Changwatthana 10, LakSi, Bangkok 10210 Phone : (66 2) 094-0800 E-mail : sale@bainisys.com Line Chat : @Bainisys

