

DS-PEA1-N1 Panic Alarm Station

DS-PEA1-N1 panic alarm station is designed without camera. It supports two-way audio. It helps to realize alarm aid the first time and provides more efficient service for building social stability. It is mainly applied to classroom, corridor, laboratory, dormitory, office, hospital, ward and so on.



▪ Key Features

- One-touch emergency calling
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC up to 128 GB
- Supports siren and audio expansion
- Vandal proof(IK 10)



▪ Specification

Detection performance	
Sound pressure	110dB, Sound Can be Configured Separately
Software features	
Tamper-Proof	tamper alarm
Intercom	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
Protocol	TCP/IP, RTSP, HIK-SIP, ONVIF
Hardware features	
Alarm input	2
Alarm output	2
Siren	1ch Siren/Light 12V/2A
Network interface	1RJ45, 10 M/100 M/1000 M self adaptive
Audio interface	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
PSTN	1
Bus	RS-485 1, Half-duplex
SD Card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G
Electrical characteristics	
Power supply	12VDC
Power Consumption	≤ 6 W
Wireless transmission	
Wired network	10 M/100 M Self-adaptive Ethernet port
General	
Operation temperature	-25 °C to +55 °C
Operation humidity	10% to 90%
Dimension(WxHxD)	170 mm× 108mm × 39.5mm(6.69" × 4.25" × 1.55")
Installation method	Wall Mounting
Audio	
Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 3 m
Audio output	1-ch 3W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output
Audio compression code rate	16Kbps, 64Kbps

▪ Available Model

DS-PEA1-N1

