

## DS-PEA12-P Panic Alarm Station

DS-PEA12 series pole panic alarm station is designed with 2 MP HD camera, 2MP HD IR camera and dual network ports. It supports scheduled turning on/off the alarm lamp, two-way audio, linking with the surrounding cameras and so on. It helps to realize alarm and aid as soon as possible and provides more efficient service for building social stability. It is mainly applied to the scenarios of school, square, tourist attraction, hospital, supermarket gate, market, station, parking lot, etc.

- One-touch emergency calling
- High quality imaging with 2 MP built-in camera
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC up to 256 GB
- Supports siren and audio expansion
- Supports standard SIP



### ▪ Specification

Software features	
Wired network	10 M/100 M Self-adaptive Ethernet port
Hardware features	
Electrical locker	Normal Cabinet Lock
Tamper-Proof	tamper alarm
Network interface	1RJ45,10 M/100 M/1000 M self adaptive
Audio interface	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
Bus	RS-485 1, Half-duplex
SD card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 256G
Loudspeaker	1-ch 30 W Build-in Loudspeaker Sound Can be Configured Separately
Video	
Resolution	1920*1080
Field angle	Horizontal field of view: 129°
Frame rate	PAL: 25fps NTSC: 30fps
Day/night switch mode	IR Cut Filter



Audio	
Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
Audio output	1-ch 30 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output
Intercom	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
Audio compression code rate	16Kbps,64Kbps
Electrical characteristics	
Operation temperature	-40 °C to +70 °C (-40 °F to 158 °F)
Power supply	110-240V AC
Operation humidity	10% to 90%
Power consumption	≤ 51 W
General	
Dimension(WxHxD)	Without Bracket: 280 mm × 280 mm × 2148 mm (11.02" × 11.02" × 84.57") With Bracket: 280 mm × 280 mm × 4332 mm (17.72" × 19.69" × 170.56")
Installation method	Ground Mounting
Device management	
Alarm input	2
Alarm output	2
Camera	2 MP HD IR Camera
Sounder output	1-ch 30 W Build-in Loudspeaker
Lamp	1 Red and Blue Alarm Lamp, Light Can be Configured Separately
Report method	
Protocol	TCP/IP, RTSP, SIP

### ▪ Available Model

DS-PEA12-P(O-STD),

