

DS-PEA3M-21H Pole Panic Alarm Station

DS-PEA3M series pole panic alarm station is designed with 2 MP HD camera, 2MP HD IR camera and dual network ports. It supports scheduled turning on/off the alarm lamp, two-way audio, linking with the surrounding cameras and so on. It helps to realize alarm and aid as soon as possible and provides more efficient service for building social stability. It is mainly applied to the scenarios of school, square, tourist attraction, hospital, supermarket gate, market, station, parking lot, etc.



▪ Key Features

- One-touch emergency calling
- High quality imaging with 2 MP built-in camera
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC up to 128 GB
- Supports siren and audio expansion
- Easy to expand the system with built-in 8-port switch
- Integrates with speed dome cameras

▪ Specification

Software features	
Wired network	10 M/100 M Self-adaptive Ethernet port
Hardware features	
Electrical locker	Electronic Controlled Cabinet Lock/Normal Cabinet Lock
Tamper-Proof	tamper alarm
Network interface	1RJ45,10 M/100 M/1000 M self adaptive
Audio interface	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
PSTN	1
Bus	RS-485 1, Half-duplex
SD card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G
Loudspeaker	110dB, Sound Can be Configured Separately



Video	
Frame rate	25fps
Field angle	Horizontal: 128° Vertical: 75° Diagonal: 147°
Day/night switch mode	IR Cut Filter
Electrical characteristics	
Power supply	110-240V AC
Operation temperature	-40 °C to +60 °C (-40 °F to 140 °F)
Power consumption	≤ 70 W
Operation humidity	10% to 90%
General	
Dimension(WxHxD)	Without Bracket: 450 mm × 500 mm × 2205 mm (17.72" × 19.69" × 86.81") With Bracket: 450 mm × 500 mm × 4500 mm (17.72" × 19.69" × 177.17")
Installation method	Ground Mounting
Audio	
Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
Audio output	1-ch 30 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output
Intercom	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
Audio compression code rate	16Kbps,64Kbps
Device management	
Alarm input	2
Camera	2 MP HD IR Camera
Alarm output	2
Sounder output	110dB, Sound Can be Configured Separately
Lamp	1 Red and Blue Alarm Lamp, Light Can be Configured Separately
Report method	
Protocol	TCP/IP, RTSP, HIK-SIP,ONVIF

▪ Available Model

DS-PEA3M-21H

