

## DS-PEA4H-10 Panic Alarm Master Station

The DS-PEA4H-10 master station supports functions such as live view, intercom, device call, etc. It is equipped with 10.1-inch high definition touch screen that displays flat-design interface. The master station applies to security areas such as school, square, hospital, shopping mall, station market, park, etc.



### ▪ Key Features

- 10.1-inch touch screen
- Real-time alarm information display
- Supports microphone rod and VGA
- Supports auto noise suppression and echo cancellation
- Easy installation with Power over Ethernet (PoE) technology

### ▪ Specification

Software features	
Intercom	Built-in Microphone, Handset、loudspeaker
Protocol	TCP/IP, HIK-SIP, and RTSP
Hardware features	
Alarm input	4
Alarm output	4
Relay output	4, relay output
Network interface	1RJ45,10 M/100 M/1000 M self adaptive
Serial port	2, RS-485 half-duplex interface
Video interface	VGA , HDMI
Audio interface	Built-in microphone, handset, and mic support
USB	1, USB 3.0 1, USB 2.0
PSTN	RJ11, 1 for handset
SD Card	1, Micro SDXC (≤ 128 GB)



Video	
Frame rate	PAL: 25 FPS, NTSC: 30 FPS
Electrical characteristics	
Power supply	12 VDC, PoE (IEEE 802.3 at/af)
Power Consumption	≤15 W
Display	
Display screen	10.1 inch colorful TFT LCD, 1280 × 800
User interface	Flat design
General	
Operation temperature	-10 °C to 55 °C
Operation humidity	10% to 90%
Dimension(WxHxD)	with handset: 361mm (14.2 inch) × 65mm (2.6 inch) × 197mm (7.8 inch) without handset: 291mm (11.5 inch) × 41mm (1.6 inch) × 197mm (7.8 inch)
Weight	≤2.5 kg (88.2 oz)
Audio	
Audio input	Built-in microphone, handset, and mic support
Audio output	Built-in loudspeaker, and handset
Audio compression code rate	16Kbps,64Kbps
Device management	
Camera	CMOS, 2 MP

### ▪ Available Model

DS-PEA4H-10

