







Inrico

Black

# SMART MULTI-MODE RADIO

The **IRC380**, developed by INRICO stands as the world's pioneering professional dual-mode terminal. Featuring a unique dual PTT button design, it seamlessly switches between wide and narrow networks, bridging the gap for "last mile" expansion and facilitating communication between public and private networks. With capabilities encompassing real-time voice and video transmission, instant recording, upload of recorded content, and information reporting, the IRC380 not only ensures continuous interaction with frontline operators but also enables coordination with rear emergency command personnel. This significantly enhances operational efficiency during on-site activities.

## **SCENARIOS**













Energy Transportation Rail

## **PRODUCT PARAMETERS**

HARDWARE	
RAM+ROM	2GB+16GB
Expand Memory	up to 32G
Card Slot	Dual SIM Card+ TF Card
Interface	M6
OTG	Support, via the M6 interface
Screen	2.4 Inches, 480 x 640
Camera	Front camera 5.0MP; Rear camera 13.0MP,120°ultra-wide angle
Speaker	Ø36mm waterproof speaker, 8Ω 3W
Microphone	Master-microphone+Slave-microphone +Noise-cancelling microphone
Battery	3100mAh(Removable),4000mAh(Optional),7.6V
Dimension	Thin Battery: 162.3 x 61x 34.5mm(Without Belt Clip and Antenna)
	Thick Battery:162.3 x 61 x 38mm(Without Belt Clipand Antenna)

CERTIFICATION	
Drop	1.5m
Ingress Protection	IP68
Certification	CE/FCC/MIL-STD-810H/GMS

CONNECTION		
Frequencies	2G: B2/B3/B5/B8	
	3G:B1/B2/B4/B5/B8	
	4G-FDD:B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B26/B28/B66	
	4G-TDD:B38/B39/B40/41	
Wi-Fi	IEEE 802.11 a/b/g/n/ac/k/v/r, 2.4G/5G	
Bluetooth	BLE 5.0	
NFC	Support	
Navigation	GPS, GLONASS, AGPS	

Frequency Range  UHF: 400-480MHz, VHF: 136-174MHz  Channel Capacity  2048  Channel Spacing  25KHz/12.5KHz  Power Output  UHF: High Power 4W/ Low Power 1W VHF: 5W  Receiver Sensitivity  ≤-123dBm  DMR Encryption  ARC4 / AES128 / AES256	DMR	
Channel Spacing 25KHz/12.5KHz  Power Output UHF: High Power 4W/ Low Power 1W VHF: 5W  Receiver Sensitivity ≤-123dBm  DMR Encryption ARC4 / AES128 / AES256	Frequency Range	UHF: 400-480MHz, VHF: 136-174MHz
Power Output UHF: High Power 4W/ Low Power 1W VHF: 5W  Receiver Sensitivity ≤-123dBm  DMR Encryption ARC4 / AES128 / AES256	Channel Capacity	2048
Receiver Sensitivity ≤-123dBm  DMR Encryption ARC4 / AES128 / AES256	Channel Spacing	25KHz/12.5KHz
DMR Encryption ARC4 / AES128 / AES256	Power Output	UHF: High Power 4W/ Low Power 1W VHF: 5W
71 7.1.0.1,7120.120,7120.200	Receiver Sensitivity	≤-123dBm
	DMR Encryption	ARC4 / AES128 / AES256
License Agreement Tier II	License Agreement	Tier II

OS	
OS	Android 10

### STANDARD ACCESSORIES

**Charging Cable** Power Adapter Belt Clip Battery Strap Antenna

# **OPTIONAL ACCESSORIES**

Programming Cable Bluetooth RSM M6 Headphone M6 Desktop Charger Remote Speaker Microphone



Address : 117/8, Changwatthana 10, LakSi, Bangkok 10210

Line :@Bainisys Phone: (662) 094-0800 Web: www.inrico-thailand.com

